

HORIZONTALLY-MOUNTED ENAIRGY BOX SERIES

Petrol and diesel Box compressors - air or electrical power

This horizontally-mounted petrol compressor from Guernet's Box range will be ideal for your **LV and/or HGV work vehicles**. All features are at your fingertips. Its **50L air tank** ensures an optimum working time. Its low height will allow you to arrange shelves or other items above. The panels are easily removable for nearby maintenance and use.

EQUIPMENT

- Electric starter and battery kit
- Exhaust hose with floor feedthru



Models shown from top to bottom BOXTLO72DE

FEATURES



CYLINDER
cast iron for the entire range

- **TANKS**
CE approved
- **12 VOLT TIME COUNTER**

OPTIONAL

- **DIFFERENTIAL PROTECTION** apart from 7kVA and BOXTLO72DE
- **AIR TANKS ACCORDING TO NEEDS** available as 3, 50 or 120L versions
- **12 VOLT AUTOMATIC DRAIN**

HORIZONTALLY-MOUNTED PETROL ENAIRGY BOX SERIES

Petrol Box compressors - air or electrical power

MODEL	CYL. / STAGE	PRESSURE (BAR)	POWER (HP)	AIR DISPLACEMENT (L/MIN-M ³ /H)	ENGINE (type)	TANK (L)	GENERATOR (kVA /Watts)	DIMENSIONS (L x w x H)	WEIGHT (KG)
BOX T38 ES G	2/2	12	6,3 - 8,4	600 / 36	GX270QXE	50	2,6 kva mono	1470 x 960 x 1040	170
BOX T38 ES G6M	2/2	12	8,7 - 11,7	600 / 36	GX390QXE	50	6 kva mono	1470 x 960 x 1040	180
BOX T38 ES G7T	2/2	12	8,7 - 11,7	600 / 36	GX390QXE	50	7 kva tri / 2,4 kva mono	1470 x 960 x 1040	190
BOX T53 ES G	2/2	12	8,7 - 11,7	967 / 58	GX390QXE	50	2,6 kva mono	1470 x 960 x 1040	185
BOX T53 ES G6M	2/2	12	8,7 - 11,7	967 / 58	GX390QXE	50	6 kva mono	1470 x 960 x 1040	195
BOX T53 ES G7T	2/2	12	8,7 - 11,7	967 / 58	GX390QXE	50	7 kva tri / 2,4 kva mono	1470 x 960 x 1040	205
BOX T53 ES G BK	2/2	12	8,7 - 11,7	700 / 42	GX390QXE	50	2,6 kva mono	1470 x 960 x 1040	175
BOX T53 ES G6MBK	2/2	12	8,7 - 11,7	700 / 42	GX390QXE	50	6 kva mono	1470 x 960 x 1040	185
BOX T53 ES G7TBK	2/2	12	8,7 - 11,7	700 / 42	GX390QXE	50	7 kva tri / 2,4 kva mono	1470 x 960 x 1040	195

- Pressure adjustment to specify when ordering.
- Protection differential on 7kVA three-phase models.

HORIZONTALLY-MOUNTED DIESEL ENAIRGY BOX SERIES

Diesel Box compressors - air or electrical power

MODEL	CYL. / STAGE	PRESSURE (BAR)	POWER (HP)	AIR DISPLACEMENT (L/MIN-M ³ /H)	ENGINE (type)	DASHPOT	TANK (L)	GENERATOR (kVA /Watts)	DIMENSIONS (L x w x H)	WEIGHT (KG)
BOX TLO38 DG	2/2	12	7,5 - 10,1	667 / 40	KD15-440	✓	50	2,6 kva mono	1435 x 990 x 1110	240
BOX TLO38 DG	2/2	12	7,5 - 10,1	667 / 40	KD15-440	✓	50	6 kva mono	1435 x 990 x 1110	250
BOX TLO38 DG7T	2/2	12	7,5 - 10,1	667 / 40	KD15-440	✓	50	7 kva tri / 2,4 kva mono	1435 x 990 x 1110	260
BOX TLO54 DG	2/2	12	7,5 - 10,1	1050 / 63	KD15-440	✓	50	2,6 kva mono	1435 x 990 x 1110	250
BOX TLO54 DG6M	2/2	12	7,5 - 10,1	1050 / 63	KD15-440	✓	50	6 kva mono	1435 x 990 x 1110	260
BOX TLO54 DG7T	2/2	12	7,5 - 10,1	1050 / 63	KD15-440	✓	50	7 kva tri / 2,4 kva mono	1435 x 990 x 1110	270

- Pressure adjustment to specify when ordering.
- Protection differential on 7kVA three-phase models.



Easy accessibility and easy maintenance.



Air tank which can be separated provided with all safety devices: pressure gauge, safety valve, drain valve, air outlet valve and plugs.

ADVANTAGES

- The workshop truck compressor with the lowest height on the market .
- Possibility of using only one power source at a time except on certain models (BOXT53ESG).
- Unloading valve to facilitate cold starting.

DIFFERENTIAL NOTE: We recommend you choose the differential opt on. This option is not mandatory but protects individuals in the event of electrical leakage on the compressor when using electrical appliances. This equipment may be required by an inspection agency if you use portable electrical appliances at a distance of more than one metre from the power source.

* Dimensions and weight are given as indications only and may change at any time. Any specific request may be considered upon mere consultation. Photos may differ from actual product