



Non-contractual illustrations

ADVANTAGES

- Low noise level
- Belt and pulley transmission
- Star-delta starting
- Smart, simple control panel
- High-performance ventilation system
- IE3 / S1 high performance electric motor
- Supplied with 3 metres of power cable

This compressor is ideal for all industrial applications.

Efficiency, flow rate, size, manageability, silence and elegant design give this compressor a unique character, where the emphasis is above all on performance and efficiency.

100%
LOAD RATE



FEATURES

VOLTAGE / FREQUENCY	400 V 3-phase / 50 Hz
NOMINAL CURRENT INTENSITY	approx. 24 A
RECOMMENDED CIRCUIT BREAKER	32A curve D
ELEC. MOTOR POWER	11 kW - 15 hp
REAL FLOW RATE AT 8 BAR	90 m³/h - 1500 L/min
MAX PRESSURE	10 BAR

AIR OUTLET	1 direct G3/4" - F
SOUND LEVEL	68±2 dB(A) at 1 meter
OPERATING TEMPERATURE	5 - 40°C
DIMENSIONS *	See dimensions below
NET WEIGHT *	325 kg

* Weights and dimensions are given for information only and may change at any time.

A screw compressor requires an electrical installation fitted with a four-pole curve D circuit breaker with an aM motor fuse.
Check your electrical installation before purchasing any compressor.

OPTION

KHG Frost protection kit

Contact us

Please contact us for information.

By mail contact@guernet.com • By phone +33 (0)3.45.88.30.30

Address 51 Route de Montargis - 89300 Joigny (FRANCE)

www.Guernet.com

GV15

Compresseur à vis électrique insonorisé 15HP 400V

VUES D'ENCOMBREMENT

